

# THYRA

## Human Machine INTERFACE HMI



### ◀ RELIABILITY TEST



ESD TEST



EXTREME TEMP. TEST



IMPULSE TEST



THUNDER WAVE TEST

# Product Specification

<b>Hardware</b>	Specification	AMZ101P24
	Screen	3" ~10.1" TFT LCD
	Definition (Px)	1024X600
	Color order index	260,000
	lightness	250 cd/m2
	BG light	LED
	LED LIFESPAN	20,000h
	Touching screen	Capacitor type
	CPU	2-bit 600MHz & ARM9 32MB DDR INBUILD
	Storage	128Mbyte SPI Nand Flash
	RTC	Clock inbuild
	Power off Data storage	Support
	U disk	Support
	Communication	COM1: RS232,RS485, COM2: RS232,RS485,Ethernet
<b>Regulation</b>	Rated power	<3.5W
	Rated voltage	DC 10-30V
	Power protection	IEC61000-6-2:2005, IEC61000-6-4:2007
	Power loss	<5ms
	CE&ROHS	IEC61000-6-2:2005, IEC61000-6-4:2007
<b>Environment Regulation</b>	Working temp.	-20℃~50℃
	Storage temp.	-40℃~70℃
	Environment humidity	10~90%RH
	Anti-shake	10-25Hz (X、Y、Z direction, 2g/30minutes)
	Cooling way	Wind cool
<b>Others</b>	Protection grade	Front board IP65 & back board IP20
	Effect screen size	222.7*125.3mm
	Mount size	247.5*120.4mm
	Profile size	257.7*148.3mm
	Net weight	280g

## Bencera Resources LLP.

Add:710,Iscon Elegance,  
opp Karnavati Club,Next to Shapath -v  
S.G ROAD,Ahmedabad-380015.  
Tel: + 91 95120 09895/+91 97226 09663  
Email: -sales.thyra@gmail.com

**THYRA**